600AJ ARTICULATING BOOM LIFT



Performance

Platform Height 18.47 m Working Height 20.47 m Horizontal Outreach 12.10 m Up and Over Clearance 8.10 m

Swing 360 Degrees Continuous

230 kg Platform Capacity Platform Size 0.91 x 2.44 m Platform Rotator 180 Degrees Hydraulic

Jib Range of Articulation 130 Degrees (+70, -60)

Weight 11,900 kg Drive Speed 6.8 km/h Gradeability 45%

Turning Radius Outside

3.56 m Inside 1.68 m

Standard Specifications

Power Source

Diesel Engine Deutz D2011L04 Fuel Tank Capacity 113.6 L Fuel Consumption 2.46 L/hr

Hydraulic System

Capacity 115.8 L **Auxiliary Power** 12V-DC

Tyres

Standard 14 x 17.5 Foam-Filled

Standard Features

- 4WD & 4WS
- 180 Degree Hydraulic Platform Rotator
- Platform Console Machine Status Light Panel*
- AC Generator including AC Outlets to Platform
- 4 Degree Tilt Alarm/Indicator Light
- Swing Out Engine Tray
- 12V-DC Auxiliary Power
- Hourmeter
- Proportional Controls

- Control ADE® System
- Lifting/Tie Down Lugs
- Horn
- Four-Wheel Hydrostatic Drive
- Oscillating Axle
- Operator Tool Tray
- Inward Self-Closing, Self-Locking Swing Gate
- Flashing Amber Beacon
- Motion Alarm
- Glow Plugs (Diesel Engines)
- * Provides indicator lights at platform control console for system distress, low fuel and foot switch status.



Accessories & Options

- 0.91 x 1.83 m Platform
- 1/2 in. Air Line to Platform
- · Light Package
- · Platform Worklights
- · Mesh to Mid-Rail
- Special Hydraulic Oils (Consult Factory)
- · Spark Arresting Muffler
- Accessory Packages

 - SkyWelder® PackageSkyGlazier® Package
 - Nite Bright® Package
 - SkyGuard®
 - Pipe Rack
 - Cable Ladder Carrier
 - ClearSky®


Note: Some options may increase lead time, and some option combinations may not be available.


600AJ ARTICULATING BOOM LIFT



Dimensions

All dimensions are approximate.





Reach Diagram

