

VEHICLE SPECIFICATIONS

Dual Cab Flatbed



MINE-SPEC HINO 300 SERIES 3.5T DUAL CAB TRUCK - TRAY BACK

SPECIFICATIONS

	Automatic	Manual
Model	Automatic	Manual
GVM Range	4,499 to 8,000	4,499 to 8,000
GCM Range	8,000kg	GVM + 3,500kg
Power	150hp/110kW	165hp/121kW
Torque	420Nm	464Nm
Transmissions	6 spd Automatic	6 spd Manual
Wheelbase	3.9m, 4.2m	3.9m, 4.2m
Max. Nominal Body Length	4.4m, 5.0m	4.4m, 5.0m

KEY FEATURES

Pre-Collision System (PCS) including AEB & PD	Reverse Camera
Vehicle Stability Control (VSC)	ECE R-29 Cab Strength Certified
Lane Departure Warning System (LDWS)	Cruise Control**
Daytime Running Lamps (DRL)	ADR 80/03 Emission level using Euro 5 Standard
Dual SRS Airbags	Crew cab, 7 seats, 3 front & 4 rear
Rear passenger air conditioning	

STANDARD FITMENT

Tray 4.3m long x 2.3m wide	Air conditioning	Licence required - C class (standard car licence)
4,495kg GVM - 7,995kg GCM	Cruise control	Split drop sides & removable load-safe barriers
Drop sides	ABS brakes	Multimedia with Bluetooth and Android Auto/Apple CarPlay
6 speed automatic transmission	Dual airbags	Hino SmartSafe - pre-collision system with AEB and pedestrian detection, vehicle stability control, lane departure warning & reverse camera
Seats - 7	Towbar - 50mm ball - 12V connection	

EXTRA FITMENT AVAILABLE ON REQUEST

Specifications may vary depending on the vehicle