

PRODUCT SPECIFICATIONS FOR CS74B

WEIGHTS

Operating Weight - With Cab	16000 kg
Weight - Drum with Cab	10620 kg

OPERATING SPECIFICATIONS

Compaction Width	2134 mm
Turning Radius - Inside Drum Edge	3.68 m
Ground Clearance	437 mm
Static Linear Load - With Cab	49.7 kg/cm
Travel Speed - Maximum	11.4 km/h

ENGINE

Gross Power	129.5 kW
Engine Model	Cat C4.4 with ACERT

DIMENSIONS

Height - With ROPS/FOPS or Cab	3.11 m
Overall Length	6.05 m
Overall Width	2.33 m
Drum Diameter	1534 mm
Overall Width - With Blade Option	2.5 m
Drum Width	2134 mm

Wheel Base	2.9 m
Overall Length - With Blade Option	6.55 m
Optional Blade Height	688 mm

VIBRATORY SYSTEM

Centrifugal Force - Maximum	332 kN
Nominal Amplitude - Low	0.98 mm
Centrifugal Force - Minimum	166 kN
Vibratory Frequency - Standard	28 Hz (1680 vpm)
Nominal Amplitude - High	2.1 mm
Variable Frequency Option Range	23.3 - 28 Hz (1400-1680 vpm)

TIRES

Tires	23.1 x 26
--------------	-----------

SERVICE REFILL CAPACITIES

Fuel Tank Capacity	332 l
---------------------------	-------
