

PRODUCT SPECIFICATIONS FOR CW34

WEIGHTS

Operating Weight - Standard Machine Empty	10000 kg
Operating Weight - Maximum Ballast	27000 kg
Operating Weight - Maximum Wet Sand Ballast	16000 kg
Average Weight per Wheel	1620 kg
Operating Weight - No Ballast	10000 kg
Operating Weight - Maximum Water Ballast	13000 kg
Average Weight per Wheel - No Ballast	1250 kg
Average Weight per Wheel - Maximum Ballast	3380 kg

OPERATING SPECIFICATIONS

Compaction Width	2090 mm
Turning Radius - Inside (2)	6.1 m
Rolling Width	2090 mm
Turning Radius - Outside	8700 mm
Ground Clearance	260 mm
Travel Speed - Maximum	19 km/h
Turning Radius - Inside (1)	6100 mm
Number of Wheels	8

ENGINE

Bore	105 mm
Stroke	127 mm

Gross Power	98 kW
Engine Model	C4.4

DIMENSIONS

Overall Width	2160 mm
Height - Steering Wheel	2450 mm
Height - ROPS	3000 mm
Overall Length	5350 mm
Maximum Machine Height	3000 mm

TIRES

Tires	13/80 R20
--------------	-----------

SERVICE REFILL CAPACITIES

Water Spray Tank Capacity	380 l
Fuel Tank Capacity	270 l
