



D.ONE

Operating mass 1595 kg 3,516 lb 1,758 lb Axle load, avg. 798 kg 33.5 / 24.0 Drum width 850 / 610 mm Speed 1, forward / reverse 1,2 km/h 0.7 mph 1.8 mph Speed 2, forward / reverse 2,8 km/h 16,186 / 8,093 lb Centrifugal force, front / rear 72 / 36 kN 0.044 / 0.022 in Amplitude, front / rear 1,12 / 0,56 mm 2,520 / 2,520 vpm Vibration frequency 42 / 42 Hz Kohler KDW 1003 Kohler KDW 1003 Manufacturer, model Type water cooled, diesel water cooled, diesel Power 12,8 kW 17.17 hp Drive system hydrostatic hydrostatic **Emissions** Stage V, TIER4f Stage V, TIER4f



1300 BROOKS (276 657)

a sales@brookshire.com.au

mww.brookshire.com.au

BROOKS HIRE

"Better Being With Brooks"

Standard Features & Options

Hydrostatic articulated steering

Radio/cable remote control

Active Zone System

Drum extension (610/850 mm)

Dual directed-vibration system

Two travel speed ranges

Two amplitudes

Two scrapers per drum

Automatic vibration control

ECO-mode

Automatic shutdown at low oil level

Automatic engine shut down at a lateral tipping angle of 45°

Electric starter

Heavy-duty protection hood

One point lift

Special hydraulic oil

Smooth drum (-45 kg Amplitude 1.59/0.86 mm)

Portable charger for remote control battery

Adjustable scrapers 610/850 mm

Application overview

