

POWER SPECIFICATIONS:

POWER SUPPLY SOLAR INPUT ENERGY STORAGE

OPTICAL SPECIFICATIONS:

DISPLAY ARRAY

COLOURS

INTENSITY 1/2 ANGLE

DISPLAY OUTPUT

CONTROL SPECIFICATIONS:

CONTROLLER

COMMUNICATION

GPS

MECHANICAL SPECIFICATIONS:

WEIGHT TRAILER - TOWING SET-UP MAX SIZE SIGN SIZE WIND LOADING VISIBLE APPROACH SPEED

CRIMSAFE LOCK GUARD™

Nominal 12 Volts. Range 10.8 – 14.2V 350W arranged as 2 x 175 W solar array 2 x 12V 130AH maintenance free batteries Enclosed in separated locked compartment

16 PANELS as 3 LED RGBYW PIXEL ARRAY. PIXEL PITCH 30mm

YELLOW, RED, GREEN (Traffic Light Green), WHITE, BLUE

Up 15.6, Down 15.8, Kerb-side 16.3, Road-side 16.1 degrees

8,390 cd/m2 @ 100%, 114 cd/m2 @ 2% Automatic luminance control Optional, Scheduled luminance control

32 BIT HIGH PERFORMANCE MICRO-PROCESSOR INCORPORATING 2 GB INDUSTRIAL MEMORY SD

RS-232 FOR LOCAL COMMUNICATIONS
4G with 3G Fallback Mobile network and DS-Live Programming Platform*

1570mm

Satellite Tracking – Mapping display – Sign Location

Fully Galvanized Trailer and Sign frame. All steel components either galvanized or double zinc plated. All aluminum parts chromate and powder coated (checker plate excluded).

740 Kg ** if fully optioned 1590W X 2300H X 2830L (2400 DRAWBAR FOR SHIPPING) 1760W X 3600H X 2830L (OUTRIGGERS FULLY EXTENDED) 1570W X 1030H - ROTATABLE 360 DEGREES ON TRAILER As per AS 4852.2 2009 Portable Signs > 60 Kmh

Secure lock covers for locks on control/battery box



Datasign-A5 TYPE-A 5 COLOUR LED VMS

REMOTE PROGRAMING / MONITOR

DS-Live™

DS-Lite™

STANDARD DISPLAY FONTS:

1 LINE 2 LINES 3 LINES 4 LINES

AUTOFIT FONTS

DISPLAY MATRIX PREDEFINED IMAGES

CUSTOM IMAGES

ANIMATED SEQUENCES

CUSTOM ANIMATED SEQUENCES

MESSAGE SCHEDULING:

USER MANAGEMENT SYSTEM

SOFTWARE INCLUDED ON DS-LIVE™:

LTI DISPLAY

**TIME TEMPERATURE

**TRAVEL TIME DISPLAY

*Subscription Via Web based access

For all products that connect to the Data Signs Mobile Programming platform DS-Live, and is inclusive for a subscription of 1 year from date of invoice. Subsequent subscriptions are available at the standard rate as published on the DS-Live Website and purchased for each year period per unit. (Optimized for Google Chrome and Microsoft Edge)

Mobile Phone App version

FLASHING OR STATIC 0.1 TO 99 SECONDS PER FRAME

6W X 16H CHARACTER – UP TO 7 ACROSS 5W X 10H CHARACTER – UP TO 8 ACROSS 5W X 7H OR 5W X 8H – UP TO 8 ACROSS 5W X 6H UP TO 8 ACROSS

1 TO 4 LINES UP TO 12 CHARACTERS PER LINE

28H X 48W

OVER 100 SYMBOLS, PICTURES, ROAD TRAFFIC SYMBOLS

Customer created + existing range

Existing range Customer created

Week Based, Date Based, Anytime, Update @

For Hire and 3rd party users, permission based.

Lost Time Injury display – for industrial / work sites

Client pays Google direct, or for Weather & Travel Time Data & Travel Time Data, subject to service provider cost changes

*OPTIONS:

*STR

*BALLAST TANKS

*BATTERY CHARGER

*ON BOARD COMPUTER / KEYBOARD

BLUETOOTH PROGRAMING DEVICE

RADAR

**PTZ CAMERA

ADVERTISING PANELS

SPARE WHEEL

*As required by AS 4852.2 2009 Portable Signs

Solar Tilt and Rotate mechanism for optimum solar collection in low solar areas or southern states i.e. VIC, SA, TAS or NZ.

Ballast Tanks front and rear recommended for high wind regions

240V A.C. INPUT, 12V 24A OUTPUT

RS-232 INTERFACE, 40X4 LCD DISPLAY

Program your sign using Bluetooth enabled device

Radar data logging, Car Counting

Customer Mobile SIM not included

Front / Rear

REGISTRATION

Turnkey registration for VIC, NSW, QLD, WA



(276 657) 1300 BROOKS

sales@brookshire.com.au

www.brookshire.com.au