

HUGE RANGE OF NEW OPTIONS



POWER SPECIFICATIONS:

POWER SUPPLY SOLAR INPUT ENERGY STORAGE

ENDURANCE SPECIFICATION:

OPTICAL SPECIFICATIONS:

CONTROL SPECIFICATIONS:

COMMUNICATION RANGE BETWEEN MASTER-SLAVE REMOTE RANGE TO MASTER

OR OPTIONAL DIRECT WIRED LINK

REMOTE INTERNET MODE

MECHANICAL SPECIFICATIONS:

WEIGHT
TRAILERS WIDTH
TRAILER LENGTH - MASTER
TRAILER LENGTH - SLAVE
TRAILER LENGTH - COMBINATION
TRAILER HEIGHT - TOWING
SET UP HEIGHT
MECHANICAL COUPLING
LIFTER MECHANISM

TRAILER LIGHTS

CRIMSAFE LOCK GUARD™

OPERATIONAL CONTROLS:TYPE-1 OR TYPE-2 MODES POSSIBLE

USING FOLLOWING MODES

ADDITIONAL OPERATIONAL MODES

Nominal 12 Volts. Range 10.8 – 14.2V 165W 12V Solar Array - each unit 12V 135AH AGM Battery Capacity - Maintenance Free Type.

Continuous operation with a minimum of 4 hours sunlight per day.

Without sunlight, from fully a charged condition to fail-save flashing yellow mode, 7 Days.

RED, YELLOW, GREEN ASPECTS 200mm, with Automatic Dimming YELLOW REAR BEACON.

Data Signs PTL-300 Series-II Master, Slave & PTL Remote Operation as per AS 4191-2015, MRTS25 & TSI-SP-049-050-062.

900MHZ ISM SSFH Multiband, 8 channels selectable.

Up to 50m Using SmartPhone Bluetooth Remote option or 800m using dedicated long range PTL Remote option.

Using RS-485 Data Link & Cable up to 1.5Km.

*Via DS-Live™.

1.6Km line of sight.

Combined 600 Kg, 300Kg individual.

1220mm 2080mm 1260mm 3050mm 2150mm

3060mm

Easy-Link ™ Actuator Trailer Coupling System.

Electric Actuator 680mm stroke.

LED 12/24V Multi-Volt.

Secure lock covers for locks on control/battery box

PLANT CROSSING, SHUTTLE + 3 & 4 Way intersection modes GATING (SINGLE UNIT USE)

FLASHING YELLOW
MANUAL, VEHICLE ACTUATED, AUTO TIMED, AUTO RETURN

BEACON ON-OFF AUTO RETURN MODE FOR PLANT CROSSING AND SHUTTLE MODES ASPECT INHIBIT



(276 657) 1300 BROOKS

sales@brookshire.com.au

www.brookshire.com.au

SPECIFICATION DATA SHEET 2022

Datasign-PTL PORTABLE TRAFFIC LIGHT TRAILER (SET)

DS-Live™INTERNET MODE

For situations where line of sight not possible or difficult to obtain.

Must have Mobile coverage at each unit.



*Subscription Via Web based access.

For all products that connect to the Data Signs Mobile Programming platform DS-Live, and is inclusive for a subscription of 1 year from date of invoice. Subsequent subscriptions are available at the standard rate as published on the DS-Live Website and purchased for each year period per unit.

OPTIONS:

PTL LONG-RANGE REMOTE PTL BLUETOOTH REMOTE

Long Range Remote – up to 800m Bluetooth Remote – up to 50m







PTL Bluetooth Remote on Smartphone



VEHICLE DETECTORS AND	
EXTRA ROTATE BRACKET OPTION	

BATTERY CHARGER 240V A.C. input, 12V 100W output

SPARE WHEEL

DIRECT WIRED LOOM ON CABLE REEL

PEDESTRIAN CROSSING



Fitted to Front Trailer



Cable on 300m Reel (max length per reel)



🔀 Double sided light option also shown.

DOUBLE SIDED LIGHTS



Pedestrian Crossing Lights also shown.

RED TIME COUNT DOWN DISPLAY





BOOM GATE
OPTION AVAILABLE EARLY 2022



Boom Gate fitted to trailer set (storage for travel also shown).

REGISTRATION

Turnkey registration for VIC, NSW, QLD, WA



1300 BROOKS (276 657)

a sales@brookshire.com.au

www.brookshire.com.au